


AM346

225 - 400 MHz RX COUPLING UNIT

AM346 used to connect an antenna to 12 UHF receivers.
For use in defense communication systems.



TECHNICAL CHARACTERISTICS

- High dynamics active coupler
- Fixed frequency and frequency hopping compliant
- 1 monitoring output
- High linearity and 6 dB attenuation configurations
- Remote control through Ethernet SNMP
- 2U in a standard 19"

ASSOCIATED EQUIPMENTS

- UHF : Antenna AS329, AS423, AS307, AS262-2/A
- UHF: Rx coupling unit AM326

TECHNICAL DATA

RF connectors	N
Monitoring front connector	BNC
Max. Input power	+ 20 dBm
Isolation between inputs	≥ 20 dB
Insertion gain (typ.)	2.5 dB
Power supply	110 V / 220V AC
IP3	≥ 40 dB
Noise figure	≤ 7.5 dB
Dimensions	480 mm x 88 mm x 300 mm (rack 19")
Weight	5.5 kg



ALCEN
6 rue Paul Baudry
75008 PARIS – France
Tel. + 33 (0)1 40 72 55 00
alcen@alcen.com
www.alcen.com

ALSEAMAR
120 rue de La Valette-du-Var
83140 SIX-FOURS – France
Tel. + 33 (0)6 62 07 86 58
sales@alseamar-alcen.com
www.alseamar-alcen.com